PC110 Clear

SAFETY DATA SHEET

HMG Coatings (South) LTD, Faraday Park, West Portway Ind Est, Andover, Hants SP10 3SA

• Tel: (01264) 356296 • Fax: (01264) 338123 • Email: mail@hmgcoatings.co.uk • www.hmgcoatings.co.uk

(*) Denotes - See OTHER INFORMATION

PAINTS

IDENTIFICATION:

PC110 Clear

COMPOSITION / INFORMATION ON INGREDIENTS

RELEASE DATE: 08/03/2009

VOC: 0.679

ISSUE NUMBER:

MM09

| INGREDIENT NAME: | CONC % | TWA (8hr) PPM | TWA (15mins) PPM | R PHRASES |
|---------------------|--------|---------------|------------------|---------------------|
| ISO PROPANOL | 10-15 | 400 | 500 | F11 |
| TOLUENE | 20-25 | 50 | 150 SK | F11. Xn20 |
| XYLENE | 8-12 | 100 | 150 SK | 10. Xn 20/21 Xi 38. |
| METHYL ETHYL KETONE | 12-16 | 200 | 300 SK | F11 Xi 36/37. |
| BUTYL ACETATE | 12-18 | 150 | 200 | 10 |

HAZARD IDENTIFICATION

HIGHLY FLAMMABLE. EXPLOSIVE VAPOUR. IRRITATING TO RESPIRATORY SYSTEM.

FIRST AID MEASURES

| EYES: | WASH WITH WATER | |
|-------------|---|--|
| SKIN: | WASH SKIN WITH SOAP & WATER | |
| INHALATION: | HALATION: REMOVE TO FRESH AIR. GET MEDICAL AID IF UNCONSCIOUS TURN TO RECOVERY POSITION | |
| INGESTION: | DO NOT INDUCE VOMITING. GET MEDICAL AID. IF PATIENT VOMITS TURN TO RECOVERY POSITION. | |

FIRE FIGHTING MEASURES

USE CARBON DIOXIDE, DRY CHEMICAL, SAND OR EARTH. USE WATER FOG TO COOL SURFACES.

ACCIDENTAL RELEASE MEASURES

ELIMINATE SOURCES OF IGNITION. AVOID INHALING VAPOUR. EVACUATE PERSONNEL. ABSORB LIQUID WITH NON COMBUSTIBLE MATERIAL. IF PRODUCT HAS ENTERED DRAINS INFORM FIRE BRIGADE.

| HANDLING AND STORAGE | | |
|----------------------|--|--|
| USAGE PRECAUTIONS: | USE IN A FLAME PROOF AREA. FURTHER INSTRUCTIONS ON CONTAINER OR DATA SHEET. | |
| STORAGE PRECAUTIONS: | KEEP CONTAINER CLOSED. STORE IN A COOL DRY WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. NO SMOKING. | |

| PHYSICAL AND CHEMICAL PROPERTIES | | | | |
|----------------------------------|----------------------------|---|---------------------------|----|
| APPEARANCE: | LOW VISCOSITY CLEAR LIQUID | | | |
| | | | | |
| FLASHPOINT (C) : | -4 | | BOILING POINT (C) : | 79 |
| | | - | | |
| EVAPORATION RATE : | | | EXPLOSIVE LIMIT : | |
| | | - | | |
| SPECIFIC GRAVITY : | 1.22 | | SOLUBILITY @ 20 CELCIUS : | |
| | | - | | - |

PC110 CLEAR

| EXPOSURE CONTROLS AND PERSONAL PROTECTION | | |
|---|---|--|
| RESPIRATORY : | AVOID INHALING VAPOUR. USE WITH CONTROLLED EXTRACTION AND / OR APPROVED FACE MASK | |
| SKIN : | USE IMPERVIOUS GLOVES & OVERALLS | |
| EYES : | IF THERE IS RISK TO EYES USE APPROVED SAFETY GLASSES OR GOGGLES | |

STABILITY AND REACTIVITY

STABLE UNDER NORMAL STORAGE CONDITIONS.

| TOXICOLOGICAL INFORMATION | | |
|--|--|--|
| SKIN TOXICITY: IRRITATING TO SKIN. MAY BE ABSORBED. CHRONIC SKIN CONTACT MAY CAUSE DERMATITIS. | | |
| EYE TOXICITY: | IRRITATING TO EYES. | |
| INHALED TOXICITY: | MAY CAUSE DROWSINESS, NAUSEA, DIZZINESS. | |
| | | |

INGESTED TOXICITY: MAY CAUSE VOMITING, IRRITATION OF DIGESTIVE TRACT.

ECOLOGICAL INFORMATION

UNLIKELY TO BIOACCUMULATE. LOW TOXICITY TO FISH.

DISPOSABLE CONSIDERATIONS

LAND FILL IN ACCORDANCE WITH LOCAL REGULATIONS AND USING AUTHORISED PERSONNEL.

TRANSPORT INFORMATION

| UN NUMBER: | 1263 | PROPER SHIPPING NAME: PAINT | |
|----------------|------|-----------------------------|-----|
| IMDG CLASS: | 3.2 | MARINE POLLUTANT: | NO |
| PACKING GROUP: | 111 | ADR/RID: | 33. |

REGULATORY INFORMATION

| LABEL SYMBOLS: | × | ۲ | | |
|--------------------|--|--|--|--|
| RISK PHRASES: | | R11. HIGHLY FLAMMABLE. R20/21. HARMFUL BY INHALATION AND CONTACT WITH SKIN. R36/37. IRRITATING TO EYES AND RESPIRATORY SYSTEM. | | |
| SAFETY PHRASES: | S7. S9. S16. S25. AVOID SKIN AND EYE CONTACT. S29. DO NOT EMPTY INTO DRAINS. S33. TAKE PRECAUTIONS AGAINST STATIC DISCHARGE. UN 1263 PAINT RELATED PRODUCT. | | | |
| OTHER INFORMATION: | Every effort has been made to keep the information contained on this document as accurate as possible. However the company cannot be held responsible for any errors contained within. | | | |
| | * TWA EH40/2002. This information is based on our present state of knowledge. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. | | | |

PC110 CLEAR

PAGE 2 OF 2



HMG Coatings (South) LTD, Faraday Park, West Portway Ind Est, Andover, Hants SP10 3SA

• Tel: (01264) 356296 • Fax: (01264) 338123 • Email: mail@hmgcoatings.co.uk • www.hmgcoatings.co.uk