

Synergy™ PW1 Primer White

SAFETY DATA SHEET

HMG Coatings (South) LTD, Faraday Park, West Portway Ind Est, Andover, Hants SP10 3SA

• Tel: (01264) 356296 • Fax: (01264) 338123

 IDENTIFICATION:
 Synergy™ PW1 Primer White
 RELEASE DATE:
 07/06/2009
 ISSUE NUMBER:
 MM06

COMPOSITION / INFORMATION ON INGREDIENTS		(*) Denotes – See OTHER INFORMATION		VOC:	0.540	
INGREDIENT NAME:	CON	IC %	TWA (8hr) PPM	TWA (15mins) PPM	R PHRASES
METHYL ISO BUTYL KETONE XYLENE	30-35 15-25		100 100	50 150		F11. 10

HAZARD IDENTIFICATION

FLAMMABLE.

FIRST AID MEASURES

EYES:	WASH WITH WATER
SKIN:	WASH SKIN WITH SOAP & WATER. LAUNDER SOAKED CLOTHING BEFORE RE-USE.
INHALATION:	REMOVE TO FRESH AIR. GET MEDICAL AID IF UNCONCIOUS TURN TO RECOVERY POSITION.
INGESTION:	DO NOT INDUCE VOMITING. GET MEDICAL AID. IF PATIENT VOMITS TURN TO RECOVERY POSITION.

FIRE FIGHTING MEASURES

USE CARBON DIOXIDE, DRY CHEMICAL, SAND OR EARTH. USE WATER FOG TO COOL SURFACES.

ACCIDENTAL RELEASE MEASURES

ELIMINATE SOURCES OF IGNITION. AVOID INHALING VAPOUR. EVACUATE PERSONNEL. ABSORB LIQUID WITH NON COMBUSTIBLE MATERIAL.IF PRODUCT HAS ENTERED DRAINS INFORM FIRE BRIGADE.

HANDLING AND STORAGE	
USAGE PRECAUTIONS:	USE IN A FLAME PROOF AREA. FURTHER INSTRUCTIONS ON CONTAINER OR DATA SHEET.
STORAGE PRECAUTIONS:	KEEP CONTAINER CLOSED. STORE IN A COOL DRY WELL VENTILATED AREA AWAY FROM SOURCES OF IGNITION. NO SMOKING.

PHYSICAL AND CHEMICAL PROPERTIES				
APPEARANCE:	LOW VISCOSITY CLE	AR LIQUID.		
FLASHPOINT (C):	21		BOILING POINT (C):	56
		-		
EVAPORATION RATE :			EXPLOSIVE LIMIT :	
		-		
SPECIFIC GRAVITY:	0.81		SOLUBILITY @ 20 CELCIUS :	
		-		

Synergy™ PW1 Primer White

PAGE 1 OF 2

EXPOSURE CONTROLS AND PERSONAL PROTECTION				
RESPIRATORY:	INDEPENDENT AIR FED RESPIRATORS MUST BE WORN WHEN SPRAYING THIS PRODUCT AFTER MIXING WITH PARTB.			
SKIN:	USE IMPERVIOUS GLOVES & OVERALLS.			
EYES:	IF THERE IS A RISK TO EYES USE APPROVED SAFETY GLASSES & GOGGLES.			

STABILITY AND REACTIVITY

STABLE UNDER NORMAL STORAGE CONDITIONS

TOXICOLOGICAL INFORMATION			
SKIN TOXICITY:	CHRONIC SKIN CONTACT MAY CAUSE DERMATITIS.		
EYE TOXICITY:	IRRITATING TO EYES.		
INHALED TOXICITY:	MAY CAUSE DROWSINESS, NAUSEA, DIZZINESS.		

INGESTED TOXICITY: MAY CAUSE VOMITING, IRRITATION OF DIGESTIVE TRACT.

ECOLOGICAL INFORMATION

UNLIKELY TO BIOACCUMILATE. LOW TOXICITY TO FISH.

DISPOSAL CONSIDERATIONS

LAND FILL IN ACCORDANCE WITH LOCAL REGULATIONS USING AUTHORISED PERSONNEL.

TRANSPORT INFORMATION

UN NUMBER:	1263	PROPER SHIPPING NAME:	PAINT
IMDG CLASS:	3.1	MARINE POLLUTANT:	NO
PACKING GROUP:	111	ADR/RID:	33

REGULATORY INFORMATION

LABEL SYMBOLS:





RISK PHRASES: MIX RATIO 4:1.

SAFETY PHRASES: 1263 PAINT RELATED PRODUCT

OTHER INFORMATION:

Every effort has been made to keep the information contained on this document as accurate as possible. However the company cannot be held responsible for any errors contained within.

* TWA EH40/2002. This information is based on our present state of knowledge. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application.

Synergy™ PW1 Primer White

PAGE 2 OF 2



HMG Coatings (South) LTD, Faraday Park, West Portway Ind Est, Andover, Hants SP10 3SA